



Afstandsbediening / Remote Control



DH.RC.0402

geschikt voor / suitable for



DH.RC.C.2.0202

Eigenschappen

- » Alleen geschikt voor de DELTA® kettingtakel model DEH.
- » Kan achteraf worden gemonteerd en afwisselend worden gebruikt met de stuurkabel.
- » Lichte, maar robuuste zender uitgerust met noodstop.
- » Afmetingen zender (LxBxH): 205 x 60 x 53
- » Afmetingen ontvanger (LxBxH): 205 x 86 x 130
- » Voldoet aan de Machinerichtlijn 2006/42/EG.

Features

- » Only suitable for the DELTA® chain hoist model DEH.
- » Can be retrofitted and used alternately with the control cable through plug&play connection.
- » Light, yet robust transmitter equipped with emergency stop button.
- » Dimensions transmitter (LxWxH): 205 x 60 x 53
- » Dimensions receiver (LxWxH): 205 x 86 x 130
- » Complies with the Machinery Directive 2006/42/EC.



Eenvoudige plug&play-aansluiting / Easy plug&play connection

Specificaties / Specifications		
Zender		Ontvanger
Transmitter		Receiving Unit
Besturing bescherming / Control protection		IP 65
Operatiebereik vrije ruimte / Operation distance in open space		100 m
Bedrijfstemperatuur / Operating temperature		-10°C - +40°C
Netto gewicht / Net weight	0.3 kg	0.4 kg
Stroomvoorziening / Power supply	3V (2x AA)	18V - 65V

Specificaties / Specifications			
Artikelnummer	Aantal takels	Funcies	Hijssnelheid type
Article code	Number of hoists	Functions	Lifting speed type
DH.RC.0202	1	2	2
DH.RC.0402	1	4	2
DH.RC.C.2.0202	2	2	2
DH.RC.C.2.0402	2	4	2
DH.RC.C.4.0202	4	2	2
DH.RC.C.4.0402	4	4	2

2 = twee knoppen / two buttons ↓ 1 = enkele snelheid / single speed
 4 = vier knoppen / four buttons ↓ ↔ 2 = dubbele snelheid / double speed