



Afstandsbediening / Remote Control



Eigenschappen

- » Alleen geschikt voor de DELTA® kettingtakel model US en de DELTA® lieren model DKL en DPS.
- » Kan achteraf worden gemonteerd en afwisselend worden gebruikt met de stuurkabel.
- » Lichte, maar robuuste zender uitgerust met noodstop.
- » Afmetingen zender (LxBxH): 190 x 70 x 50
- » Afmetingen ontvanger (LxBxH): 175 x 125 x 75
- » Voldoet aan de Machinerichtlijn 2006/42/EG.

Features

- » Only suitable for the DELTA® chain hoist model US and the DELTA® winches model DKL and DPS.
- » Can be retrofitted and used alternately with the control cable through plug&play connection.
- » Light, yet robust transmitter equipped with emergency stop button.
- » Dimensions transmitter (LxWxH): 190 x 70 x 50
- » Dimensions receiver (LxWxH): 175 x 125 x 75
- » Complies with the Machinery Directive 2006/42/EC.



Eenvoudige plug&play-aansluiting / Easy plug&play connection

Specificaties / Specifications			
Zender		Ontvanger	
Transmitter		Receiving Unit	
Besturing bescherming / Control protection		IP 65	
Operatiebereik vrije ruimte / Operation distance in open space		100 m	
Bedrijfstemperatuur / Operating temperature		-10°C - +40°C	
Netto gewicht / Net weight	0.4 kg		1.9 kg
Stroomvoorziening / Power supply	6V (4x AA)		-

Specificaties / Specifications		
Artikelnummer	Type	
Article code	Model	
CZ.RC.US.901.902	CZ.0.US.901	
	CZ.0.US.902	
CZ.RC.US.903.904	CZ.0.US.903	
	CZ.0.US.904	
CZ.RC.DKL	CP.0.DKL.160	
	CP.0.DKL.230	
	CP.0.DKL.300	
	CP.0.DKL.500	
CZ.RC.DPS	CP.0.DPS.200	
	CP.0.DPS.250	
	CP.0.DPS.300	
	CP.0.DPS.500	
CZ.RC.DPT	CP.0.DPT.30075	
	CP.0.DPT.30151	